

Type	L #	Hits	Search Text	DBs	Time Stamp	Comments	Error Definition	Err
1	IS&R L1	4754	((385/16-18) or (359/223-226)).CCLS.	USPAT; US-PGPUB ; EPO; JPO	2004/ 07/10 13:51			0
2	BRS L2	3236	(mems or microelectromechanical) with (switch or switches or mirror or mirrors or micromirror or micromirrors or reflector or reflectors or deflector or deflectors)	USPAT; US-PGPUB ; EPO; JPO	2004/ 07/10 13:51			0
3	BRS L3	1158	(1 and 2) or 2.ti,ab.	USPAT; US-PGPUB ; EPO; JPO	2004/ 07/10 13:51			0
4	BRS L4	3777	(serpentine or corrugated) with (hinge or hinges or pivot or pivots or spring or springs or flexure or flexures)	USPAT; US-PGPUB ; EPO; JPO	2004/ 07/10 13:52			0
5	BRS L5	52	3 and 4	USPAT; US-PGPUB ; EPO; JPO	2004/ 07/10 13:52			0
6	BRS L6	140	4 same (damping or damped or damper or viscous or viscoelastic)	USPAT; US-PGPUB ; EPO; JPO	2004/ 07/10 13:53			0
7	BRS L7	13	5 and (damping or damped or damper or viscous or viscoelastic)	USPAT; US-PGPUB ; EPO; JPO	2004/ 07/10 13:54			0
8	BRS L8	152	6 or 7	USPAT; US-PGPUB ; EPO; JPO	2004/ 07/10 13:55			0
9	BRS L9	11	8 and @pd>20040103	USPAT; US-PGPUB ; EPO; JPO	2004/ 07/10 13:55			0

10/035829